

AC194-M12A Series

Compact Multipurpose Accelerometer, 4 Pin M12 Connector, 100 mV/g, ±10%



Product Features


High Performance in an Affordable, Side Exit, Compact Sensor

Very Low Noise and Superior RF Immunity

- ▶ 100 mV/g Sensitivity, ± 10%
- ▶ ± 80g Dynamic Range
- ▶ 4 Pin M12 Connector

AC194-M12A 4 Pin Connector

Connector Pin	Polarity
1	(+) Signal/Power
2	(-) Common
3	Not Used
4	Not Used



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC194-M12A	M/AC194-M12A	Environmental		
Sensitivity (±10%)	100 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	30-600,000 CPM	0,5-10000 Hz	Maximum Shock Protection	5,000 g, peak	
Dynamic Range	± 80 g, peak *Vsource ≥ 22V, 12Vbias		Electromagnetic Sensitivity	CE	
Electrical			Sealing	Welded, Hermetic	
Settling Time	<2 Seconds		Submersible Depth	200 ft.	60 m
Voltage Source (IEPE)	18-30 VDC		SIL Rating	SIL 2	
Constant Current Excitation	2-10 mA		Physical		
Spectral Noise @ 10 Hz	8 µg/√Hz		Sensing Element	PZT Ceramic	
Spectral Noise @ 100 Hz	4 µg/√Hz		Sensing Structure	Shear Mode	
Spectral Noise @ 1000 Hz	2 µg/√Hz		Weight	3.3 oz	93 grams
Output Impedance	<100 ohm		Case Material	316L Stainless Steel	
Bias Output Voltage	10-14 VDC		Connector (Non-Integral)	4 Pin M12	
Case Isolation	>10 ⁸ ohm		Resonant Frequency	1,380,000 CPM	23000 Hz
			Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
				1/4-28	M6x1